

Primacrete.

Primacrete is a ready-to-use primer with tacking effect that favors the adhesion of existing and new substrates. It is especially recommended as a bonding bridge between concrete and mortars, new and old.



Properties

- Applicable by brush or microfiber roller in one coat.
- Resistant to alkalis.
- Consolidant.
- Great adhesion power on different substrates.
- Low sensitivity to water.
- Water-based, non-flammable.
- Free of plasticizers, solvents, ammonia and emulsifiers.
- The product is supplied ready for use.

Technical data

- Aqueous Copolymer Dispersion
- Appearance: Milky liquid
- Finish: Colorless gloss
- Solids: 36.5 % Solids: 36.5
- pH: between 8 and 9
- Application temperature: 5°C to 35°C
- Dry to touch: permanent tack
- Minimum film forming temperature: 4°C
- Specific Gravity at 20°C: 1.04 g/mL
- Brookfield RVT Viscosity at 20°C (3/20 rpm): 1700 - 2200 mPa-s
- Emulsifying system: non-ionic
- Film appearance: high plasticity
- Recoatable: up to 15 days after application
- Frost stability: very good
- Outdoor stability: aliphatic
- Traffic stability: null
- Adhesion: clean and dry porous surfaces
- Maximum thickness: 60 µm

Consumption

In general:

- 0.10 L/m²

Application

The substrate must be dry, clean and firm, free of grease or oil.

- Primacrete is applied by brush or microfiber roller in one coat.
- Before applying, homogenize the product perfectly.
- Apply at temperatures between 5°C and 35°C.
- The surface must be free of dust, grease and humidity.
- Allow to dry until the product becomes translucent before applying the mortar.
- Never apply thicknesses of more than 1 cm of mortar.

Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes.

In case of contact with skin wash with soap and water.

Do not swallow. In case of ingestion do not induce vomiting and seek medical attention immediately.

It is recommended to comply with the following measures:

- Good ventilation.
- Protective goggles to avoid splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with current legal regulations.

To prevent the product from drying out or thickening close the lid after each use.

This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.

This product does not contain any harmful substances that would require, under current regulations, to take any additional measures regarding its labeling.

Keep out of reach of children.

Storage conditions

The product should be stored in its original closed container and protected from the weather at temperatures between 10°C and 30°C in a dry and well-ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, properly stored.

Packaging

Available in 5 and 25 liter containers.

Cleaning of tools

The tools are washed with soap and water, immediately after use.